

ASTROJET™ IMAGING SYSTEM II

COMPLETE IMAGING SYSTEM



Professional Inkjet Imaging System

Complete System: Friction or Shuttle Feeder, Vacuum Transport, Image Blaster Printer, Drying Unit, and 6-ft. Conveyor

- 600 x 600 DPI resolution
- Fast! Up to 30,000 pieces per hour
- Up to 8 cartridges (*4" of print area*)
- USPS certified Postnet barcode
- Windows™ True Type fonts; prints graphics and logos
- Hewlett Packard 51645A cartridge technology designed to accommodate HP bulk-ink supply
- Spot Color Capability
- Windows™ Compatible Printer Driver



Astro Machine Corp.

630 Lively Blvd.

Elk Grove Village, IL 60007

1 (847) 364-6363 • fax 1 (847) 364-9898

www.astromachine.com

inkjet
technology by 
invent

ASTROJET™ IMAGING SYSTEM II

COMPLETE IMAGING SYSTEM



Specifications:

Print Cartridges:	HP 51645A Inkjet, 6 or 8 Cartridges
Print Speed:	High: Up to 10,000 pcs/hr Standard: Up to 15,000 pcs/hr Letter: Up to 22,000 pcs/hr Draft: Up to 30,000 pcs/hr
Print Quality:	High: 600 x 600 dpi Standard: 600 x 300 dpi Letter: 600 x 200 dpi Draft: 600 x 150 dpi
Image Area:	3" or 4" depending on Printer version (6 or 8 cartridges)
Fonts:	All True Type fonts available on PC. USPS certified Postnet barcodes
Prints:	Prints graphics, logos and barcodes
Media Size:	Minimum: 3" W x 5" L (76.2 x 127 mm) Maximum: 13.5" W x 17" L (342.9 x 431.8 mm) (Varies with Feeder Capacity)
Media Thickness:	Up to 3/8" (9.5 mm) with FF-14 Friction Feeder Up to 1/2" (12.7 mm) with ASF-3000 Vacuum Shuttle Feeder
Media Type:	Open-ended Z-fold flyers, envelopes, small booklets, single sheets, card stock, and business cards
Print Colors:	Standard & Versatile Black, Red, Blue, Green, Yellow and HP Bulk Ink Cartridges
Ink:	Water-based. May require drying assistance for coated stock
Ink Monitor	Viewable on Printer Display
Diagnostics:	Resident in firmware
Firmware Update:	Flash PROM update
Memory:	64 MB
Software:	Windows™ compatible Printer Drivers
PC Interface:	Parallel or USB
Counters:	One operator resettable job counter, one permanent lifetime counter
Duty Cycle:	3 million addresses per month (<i>No duty cycle for Printer Module</i>)
Overall Dimensions:	123" W x 35" D (<i>Main Base Unit</i>) or 89" D (<i>w/Conveyor</i>) x 70" H (312.4 cm x 88.9 cm (<i>Main Base Unit</i>) or 226 cm (<i>w/Conv.</i>) x 177.8 cm)
Weight:	ASF-3000: 150 lbs. (68 kg) Image System II Base & Printer: 163 lbs. (73.9 kg) Dryer Base: 110 lbs. (49.9 kg) CD-800 Conveyor: 110 lbs. (49.9 kg)
Electrical:	220 VAC, 50/60 Hz
Options:	Printer Version: IBE-9000 Printer (<i>specify 6 or 8 Inkjet Cartridges</i>) Feeders: FF-14 Friction Feeder & Feeder Base Unit or ASF-3000 Shuttle Feeder Tabber: ATS-9950 Tabber, Labeler, Stamp Affixer (<i>w/Console</i>) CD-860 Conveyor/Stacker (<i>to add to CD-800 Conveyor</i>)

Specifications subject to change without notice.



Tasco Gent

Z.I. Asper - Legen Heirweg 59
9890 Gavere BE
Tel. +32 9 281 08 50
Fax +32 9 281 08 70
E-mail info@tasco.be

Tasco Lille

130, Boulevard de la Liberté
F-59800 LILLE
Tel. +33 3 62 26 00 22
Fax +33 3 62 26 00 23
E-mail info@tascofrance.fr

Tasco Paris

13, rue Marie Poussepin
Parc Economique Lavoisier
F-91410 DOURDAN
Tel. +33 3 62 26 00 20
Fax +33 3 62 26 00 23
E-mail info@tascofrance.fr

Site www.tasco.be - www.tascofrance.fr - Webshop www.tashop.eu